



Project Name:	
Location:	
Item #:	

# PBF 15.0 Blast Chiller/Freezer

## **BLAST CHILLER/FREEZER SPECIFICATIONS**

This unit fits perfectly into a professional kitchen workflow, making it possible to practice HACCP guidelines concerning the cook/chill concept. The unique ambient chill method and Indirect air circulation help to assure better food quality and safety.

Manufactured with the environment in mind, it includes advanced technology and important features to protect your long-term investment. Along with colder product temperatures, it offers lower utility costs, improved food safety and an excellent value in today's foodservice marketplace.

#### CAPACITY

15 pans 18" x 26" x 1" deep Pans not included

**DISTANCE** between shelves 2.69"

# **OUTSIDE DIMENSIONS**

32.25" (W) x 35" (D) x 78.25" (H)

# INTERIOR DIMENSIONS

27.5" (W) X 19.5" (D) X 43" (H)

WEIGHT: 520 lbs

# SHIPPING DIMENSIONS:

34" (W) X 38" (D) X 84" (H)

SHIPPING WEIGHT: 560 lbs

#### **OUTPUT CHILLING CAPACITY**

+194/+37°F 110 lbs within 90 minutes

#### **OUTPUT FREEZING CAPACITY**

+194/0°F 70 lbs within 240 minutes

# **OUTPUT THAWING CAPACITY**

0°F/38°F 22 lbs within 240 minutes 0°F/38°F 44 lbs within 480 minutes 0°F/38°F 66 lbs within 720 minutes

#### **HEAT LOAD BTU/HR:** 16,578

- 10° F evaporator temperature/104° F ambient

# **ELECTRICAL SUPPLY:**

208-240 V/1 PH/60 Hz (3 PH optional)

**RLA/LRA/MOP:** 12/102/33

40 A circuit, #8 wire required

# STANDARD FEATURES

- Ambient chill method
- · Indirect air circulation to improve food quality
- HACCP compliant; self-contained refrigerated system
- Electronic touch screen control; user friendly and programmable for up to 99 recipes
- USB port; front mounted for easy access to download data, such as HACCP, or upload recipes
- Automatic hot gas defrost
- · Rounded interior corners for simple cleaning
- · Single point product probe
- · Slide out refrigeration system for efficient service access
- Stainless steel rack system for pans or shelves
- Snap-in magnetic gasket for straightforward changes or cleaning
- · Self-closing door, right-hand hinged
- · Casters for effortless movement, front casters can be swivel, fixed or locked
- 304 Stainless steel interior and exterior front, sides, and top.
- Refrigerant: R404
- Environmentally friendly HFO insulation

#### WARRANTY

- Three year warranty on parts and labor
- Additional warranty for years 3-5 on compressor (parts only)

# **OPTIONAL ACCESSORIES**

- · Plastic coated shelves
- UV sanitizer
- · Heated multi-point probe
- · Three core probe kit
- · Left-hand door
- Door bolt lock

Specifications subject to change without notice.



Superior Quality Made in Italy











Proud to be family-owned